



Deep Cycle – Lithium

Our deep cycling batteries are engineered to cater to a vast array of applications. Designed for the Australian market, our batteries incorporate quality and durable materials to deliver reliable and sustained cycling performance.

Features:

- Maintenance free with a durable, fully sealed construction
- High cycle life
- Integrated Battery Management System (BMS) with voltage, temperature & short circuit protections
- Light weight and suitable for multi angle fitment
- Superior charge and discharge performance

Applications

- Caravan, Campervan and Trailer
- Marine & 4x4 Dual Battery System

Specifications:

Technology	Lithium
Voltage	12
Capacity (20hr)	40Ah
Length	194mm
Width	132mm
Height	170mm
Nominal weight	5.5Kg
Assembly	D
Post	M6
Max Charge Voltage	14.6 ± 0.1V
Cut off Voltage	10V
Max. Discharge Current	50A
Max. Pulse Discharge Current (3 Sec)	150A
Max. Charge Current	40A
Recommended Current Charge	≤ 20A
Cycle Life (100% DoD)	≥ 2000
Operating Temp - Charge	0 - 50°C
Operating Temp - Discharge	-20 - 55°C
Short Circuit Release	Load Release
Max. Series / Parallel Configuration	4P or 4S

Club Assist

Eagle House, Level 8, 473 Bourke Street, Melbourne Victoria 3000
(03) 9797 8600 | clubassist.com.au

Post Assembly



Post Type

