



Deep Cycle – Lithium

Our deep cycling batteries are engineered to cater to a vast array of applications. Designed for the Australian market, our batteries incorporate quality and durable materials to deliver reliable and sustained cycling performance.

Features:

- Maintenance free with a durable, fully sealed construction
- High cycle life
- Integrated Battery Management System (BMS) with voltage, temperature & short circuit protections
- Light weight and suitable for multi angle fitment
- Superior charge and discharge performance

Applications

- Caravan, Campervan and Trailer
- Marine & 4x4 Dual Battery System


Specifications:

Technology	Lithium
Voltage	12
Capacity (20hr)	300Ah
Length	518mm
Width	271mm
Height	222mm
Nominal weight	35Kg
Assembly	D
Post	M8
Max Charge Voltage	14.6 ± 0.1V
Cut off Voltage	10V
Max. Discharge Current	180A
Max. Pulse Discharge Current (3 Sec)	450A
Max. Charge Current	150A
Recommended Current Charge	≤ 100A
Cycle Life (100% DoD)	≥ 2000
Operating Temp - Charge	0 - 50°C
Operating Temp - Discharge	-20 - 55°C
Short Circuit Release	Load Release
Max. Series / Parallel Configuration	4P
Bluetooth Connectivity	Yes

Post Assembly



Post Type



Club Assist

Eagle House, Level 8, 473 Bourke Street, Melbourne Victoria 3000
(03) 9797 8600 | clubassist.com.au